



EasyBloodGas

Blood Gas Analyzer

Easy inside and out

with easy blood gas medica has redefined blood gas analyzer design

Medica's EasyBloodGas analyzer measures pH, PCO₂ and PO₂ and calculates eleven additional parameters. Patient parameters, including FIO₂ and Hb, can be entered using the digital keypad and integrated into patient results. Measured and calculated results are displayed and printed. Simple menus guide the user through analyzer operation. The modular design makes maintenance easy.

EasyBloodGas focuses on the laboratory's need to deliver sample results economically.

Unique electrode design, combined with precise control of calibrator volumes, ensure economical operation and a low cost per sample.

gas analyzers has been packaged in a new compact format with a small footprint to save space. Gas tanks are eliminated. Gas and liquids have been mixed (tonometered) to create a convenient Reagent Module containing liquid calibrants. All components are combined into three simple modules, easily accessible by the user. Routine maintenance is limited to the replacement of electrodes and a single pump tube.

Blood gas analyzer operation has never been simpler

The Universal Sampler adapts to both syringe and capillary samples.

The sample probe's self-wiping feature provides convenience, sample integrity and user safety.

use Compact reagent module for convenience, economy and safety

Bulky gas tanks are replaced with liquid, tonometered calibrants, packaged in a convenient Reagent Module which also collects waste, protecting the user from biological hazards.

The Reagent Module's solid-state memory enables

EasyBloodGas to track date code and reagent usage.

Operation without interruption is assured.

Disposable, maintenance-free electrodes

Advanced membrane technology and novel packaging bring unprecedented convenience to electrode replacement.

Medica's integral membrane design means that membranes never

need to be changed by the user, saving time and simplifying maintenance.



Simple menu-prompted operation with a touch of the keypad

EasyBloodGas can be programmed to conform with established lab protocols. The software allows selection of desired options, including Reference Limits, Quality Control Limits, Operator ID and Patient Data.

HOME MENU	DIAGNOSTICS	SETUP MENU
1. ANALYZE SAMLE	1. TEST COMPONENTS	1. USER OPTIONS
2. ANALYZE QC	2. TEST FLUIDICS	2. CONFIGURATION
3. CALIBRATE	3. SENSOR STATUS	3. PRINTER OPTIONS
4. DAILY CLEANER	4. PRIME FLUIDS	4. SET REFERENCE LIMITS
5. SECOND MENU	5. PRINT mV's	5. PATIENT INFORMATION
		6. DELETE DATA

Easy to maintain Maintenance

waste Easy Electrolytes can be maintained by anyone, anytime, anywhere

Innovative design simplifies maintenance, addressing the needs of the remote laboratory with limited access to technical service personnel. All service calls can be performed by fax or telephone, eliminating the need for on-site service. Diagnostic software displays component status, assuring quick troubleshooting. Modularity makes assembly and disassembly quick and easy. waste Easy Electrolytes can be maintained by anyone, anytime, anywhere. Removal of the three plug-in modules—Reagent Module, Sensor Module and Valve Module—is accomplished without tools.

Easy data management

Comprehensive quality control and data management

management The EasyBloodGas quality control program calculates and stores complete statistics for the last 30 quality control results at each of three levels. A printed Levey-Jennings chart visually identifies trends. The data management program compares all patient results with ranges stored in memory and flags out-of-range results. Results are stored in memory for up to 64 patients.



Specifications

CLIA Classification: Moderate complexity
 Sample Type: Whole blood
 Sample Size: 100 µL Syringe 75 µL Capillary

Measured Parameters

pH 6.900 – 7.900 pH units
 PCO₂ 8.0 – 150.0 mmHg
 PO₂ 10 – 700 mmHg

Calculated Parameters

pH (T) (pH temperature corrected)
 PCO₂ (T) (PCO₂ temperature corrected)
 PO₂ (T) (PO₂ temperature corrected)
 TCO₂ (Total Carbon Dioxide) 0 – 50 mmol/L
 HCO₃⁻(Bicarbonate) 0 – 50 mmol/L
 BE_b (Base Excess in blood) -25.0 – 25.0 mmol/L
 BE_{ecf} (Base Excess in extra cellular fluid) -25.0 – 25.0 mmol/L
 SBC(Standard Bicarbonate) 0 – 50 mmol/L
 %SO₂C(Oxygen Saturation calculated at normal P50) 40.0 – 100.0%
 A-aDO₂ (Alveolar arterial oxygen gradient) 0 – 700 mmHg
 RI(Respiratory Index) 0.0 – 70.0


Input Parameters

Patient Temperature 5 – 45°C
 Hemoglobin 30 – 30.0 g/dL
 FIO₂ 10 – 100%
 Patient ID 14 digits


Sample Temperature Control: 37°C ±0.2°C
 Ambient Conditions: 15 – 30°C (59 – 86°F), 500 – 800 mmHg (max 15 PSI) 5 – 85% relative humidity, non-condensing atmospheric air environment (21% PO₂)

Analysis Time: 125 seconds
 Data Storage: 64 Patient results with Operator ID, Patient ID, Date and Time QC – up to 30 results for each Level (1, 2, 3)
 Calibration: Automatic or On-Demand
 Input/Output: Numeric keypad, graphic display, 27 column thermal printer, barcode reader port, RS-232 computer interface port
 Power: 100/115 ~ VAC, 50 – 60 Hz, 0.8 A or 220 ~ VAC, 50 – 60 Hz, 0.4A
 Size & Weight: 14.5" W x 12.5" H x 7" D (37 cm W x 32 cm H x 18 cm D) 16 lbs. (7.3 kg) with reagent module


MOGADISHU OFFICE

 +252 61 5000491
 +252 1 656503


HARGEISA OFFICE

 +252 63 4440909
 +252 2 512422

GAROWE OFFICE

 +252 90 7742425
 +252 90 7662918

DJIBOUTI OFFICE

 +253 77 021504
 +253 77 189595